


QUICK START GUIDE

RF-PRO BATTERY CO UNIT

Please read through all of the steps thoroughly before installation.


DO THIS BEFORE YOU INSTALL ANY OF THE DEVICES!

- 1.** Working on a table top, activate the alarms by sliding the switch inside the screw mounting hole upwards, with a small screwdriver. Place the alarms to your right. ****N.B. When you activate the alarm, it makes a VERY LOUD chirp!****



- 2.** On the first alarm (doesn't matter which) hold down the TEST/SILENCE button for 12 seconds, until the red LED stays lit (ignore any other flashing LED's while holding the button). This alarm is now in pairing mode.

The red LED will stay lit for 30 seconds.
Place this alarm directly in front of you.



- 3.** While the red LED is lit on the first alarm, to add other CO alarms to the Home Group, take one from your right and press the TEST/SILENCE button **firmly and slowly** twice with a pause between taps, so that the red and green LED's flash once with each press. The red LED will then flash 3 times.

N.B. If the red LED goes out on the first alarm, repeat Step 2 for that alarm.

- 4.** Repeat Step 3 for any additional alarms you want to pair.

- 6.** The alarm can then be installed into its location. If you want to turn it off for any reason (see full user manual), the alarm will remain paired.

- 7.** When all alarms are installed, repeat Step 5 to test, and ensure they all sound.

- 5.** When you have paired all of the alarms, you can test the CO alarms by holding the TEST/SILENCE button for 3 seconds – sounder chirps 4 times and red LED flashes for 30 seconds. Other paired alarms should also sound.

HISPEC

LIGHTING • FIRE & CO DETECTION

For more information consult the instruction manual.