


Geberit Mapress Copper T-piece, equal



Example image



Application purposes

- For cold and hot potable water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For district heating water ≤ 120 °C
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54$ mm
- Seal ring made of CIIR, black, up to $\varnothing \leq 54$ mm
- Seal ring made of EPDM, black, from $\varnothing > 54$ mm
- Pressing socket with transparent protection plug

Technical data

Product material | Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, \varnothing	arc	L	L1	l	Z	Z1
61000	10	12 mm	90°	6.2 cm	3.1 cm	3.1 cm	1.4 cm	1.4 cm
61002	12	15 mm	90°	6.4 cm	3.1 cm	3.2 cm	1.2 cm	1.2 cm
61003	15	18 mm	90°	6.8 cm	3.4 cm	3.4 cm	1.4 cm	1.4 cm
61004	20	22 mm	90°	7.4 cm	3.7 cm	3.7 cm	1.6 cm	1.6 cm
61005	25	28 mm	90°	8.4 cm	4.2 cm	4.2 cm	1.9 cm	1.9 cm
61006	32	35 mm	90°	10 cm	5.9 cm	5 cm	2.4 cm	3.3 cm
61007	40	42 mm	90°	11.4 cm	6.6 cm	5.7 cm	2.7 cm	3.6 cm
61008	50	54 mm	90°	13.8 cm	7.8 cm	6.9 cm	3.4 cm	4.3 cm
61010	65	66.7 mm	90°	22 cm	10.5 cm	11 cm	6 cm	5.5 cm
61011	65	76.1 mm	90°	23 cm	11.0 cm	11.5 cm	6.2 cm	5.7 cm
61012	80	88.9 mm	90°	26 cm	12.7 cm	13 cm	7 cm	6.7 cm
61013	100	108 mm	90°	31 cm	15.3 cm	15.5 cm	8 cm	7.8 cm