


Geberit Delta concealed cistern 12 cm, 6/3 litres, with Delta20 flush plate



Application purposes

- · For drywall construction
- For installation in part or room-height prewall installations
- For installation in room-height installation walls
- For floor-standing WCs

Characteristics

- · Concealed cistern with front actuation
- · Concealed cistern, fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II

- · Immediate post flush possible with factory setting
- · Flush bend fitted
- · Water supply connection on the rear or top centre
- Connection hose on angle stop valve can be attached without tools

Technical data

Flow pressure	0.1-10 bar
Maximum operating temperature, water	25 °C
Flush volume, factory setting	5.8 and 3 l
Flush volume small, adjustment range	3-41

Scope of delivery

- Angle stop valve R 1/2", compatible with MF, with adapter ring
- Protection box for service opening, made of polystyrene foam
- 2 distance bolts
- Flush bend 90°
- · Protection plug

- · Fastening for flush bend
- Flush bend extension, ø 45 mm
- Cup for flush volume reduction 4.0 / 2.6 l
- 2 fixing brackets
- · Fastening material

Art. no.	Colour / surface	В	Н	Т	
109.103.21.2	gloss chrome-plated	41 cm	44.5 cm	12 cm	New