


Geberit Mapress Copper cap



Example image



Application purposes

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water ≤ 120 °C
- For service water and process water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

- For permanent termination of pipe ends

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54$ mm
- Seal ring made of CIIR, black, up to $\varnothing \leq 54$ mm
- Seal ring made of EPDM, black, from $\varnothing > 54$ mm
- Pressing socket with transparent protection plug

Technical data

Product material | Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, \varnothing	L	Z
60231	10	12 mm	2 cm	0.3 cm
60232	12	15 mm	2.3 cm	0.3 cm
60233	15	18 mm	2.3 cm	0.3 cm
60234	20	22 mm	2.5 cm	0.4 cm
60235	25	28 mm	2.7 cm	0.4 cm
60236	32	35 mm	3 cm	0.4 cm
60237	40	42 mm	3.4 cm	0.4 cm
60238	50	54 mm	3.9 cm	0.4 cm
60239	65	66.7 mm	5.9 cm	0.9 cm
60240	65	76.1 mm	6.4 cm	1.1 cm
60241	80	88.9 mm	7.1 cm	1.1 cm
60242	100	108 mm	8.6 cm	1.1 cm