


Geberit Mapress Copper bend with plain end (gas)



Example image



Application purposes

- For natural gases
- For liquefied gases
- For natural and liquefied gases

Characteristics

- Pressing indicator

- Leaky if unpressed
- Marked in yellow
- Seal ring made of HNBR, yellow
- Pressing socket with yellow protection plug

Technical data

Product material | Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, ø	arc	L	H	Z
34507	12	15 mm	90 °	3.8 cm	5.1 cm	1.8 cm
34521	12	15 mm	45 °	2.8 cm	3.8 cm	0.8 cm
34522	15	18 mm	45 °	2.9 cm	3.9 cm	0.9 cm
34508	15	18 mm	90 °	4.2 cm	5.3 cm	2.2 cm
34523	20	22 mm	45 °	3.2 cm	4.4 cm	1.1 cm
34509	20	22 mm	90 °	4.7 cm	6 cm	2.6 cm
34524	25	28 mm	45 °	3.7 cm	4.5 cm	1.4 cm
34510	25	28 mm	90 °	5.7 cm	6.5 cm	3.4 cm
34525	32	35 mm	45 °	4 cm	4.9 cm	1.4 cm
34511	32	35 mm	90 °	6.5 cm	7.4 cm	3.9 cm
34526	40	42 mm	45 °	4.7 cm	5.7 cm	1.7 cm
34512	40	42 mm	90 °	7.6 cm	8.6 cm	4.6 cm
34527	50	54 mm	45 °	5.7 cm	6.8 cm	2.2 cm
34513	50	54 mm	90 °	9.5 cm	10.6 cm	6 cm