



Available Finishes - Sleeving Kit		
Light Pewter	Matte Metallic Grey	
Brass	Gunboat Grey	
Un-Lacquered Brass	Antique Brass	
Chrome	Antique Copper	
Brushed Copper	Polished Copper	
Nickel	Black	
Brushed Brass	Satin Nickel	
Old English Brass	Pewter	
Metallic Grey	Textured Black	

Connection Size		
Valve to Radiator	N/A	
Valve to Pipe	N/A	

Allen Key size		
To adjust Lock-Shield	N/A	
To fit Coupler to Radiator	N/A	
Allen Keys are not included		

Pressure Ratings		
Max Test Pressure	N/A	
Max Operating Pressure	N/A	
Max Differential Pressure	N/A	
Pressure Drop Value (Kvs)	N/A	

Kvs value is the metric measure for the flow of a fully opened valve. It is defined as: The volume flow in cubic metres per hour of water at a temperature of between 5° and 40° Celsius with a pressure drop across the valve of 1 bar.

Flow Ratings		
Normal Flow Rate	N/A	
Max Flow Rate	N/A	

Temperature Ratings		
Max Test Temperature	N/A	
Max Operating Temperature	N/A	
Temperature Adjustment Range	N/A	

Disclaimer

All dimensions are approximate and for roughing in only. We reserve the right to alter dimensions without notice. We recommend no work be carried out until the goods arrive. We can take no responsibility for errors in information supplied.

