

Data sheet for item 73516400

Fränkische profitherm MLC pipe grey in coils 16x2 - 100 m



MASTERDATA

| | |
|-----------------------|---------------|
| Item type | Product |
| GTIN | 4013960357790 |
| Content unit | Meter |
| Order unit | Meter |
| Content quantity | 1 Meter |
| Price quantity | 1 |
| Min. order quantity | 1800 Meter |
| Order step | 1800 Meter |
| Customs tariff number | 39173900 |



Data sheet for item 73516400

FEATURES

ETIM 9.0: Multi-layered pipe, smooth (EC010225)

| | |
|--|-----------------|
| Material inner layer | Plastic |
| Quality class inner layer | PE-RT II |
| Material intermediate layer | Aluminium |
| Quality class intermediate layer | Other |
| Material outer layer | Plastic |
| Quality class outer layer | PE-RT II |
| Number of layers | 5 |
| Glass-fibre reinforced | No |
| Diffusion-proof | Yes |
| Nominal diameter | DN 12 |
| Outer pipe diameter | 16 mm |
| Wall thickness | 2 mm |
| Thickness intermediate layer | - |
| System-specific | Yes |
| Medium temperature (continuous) | 0 °C - 70 °C |
| Max. medium temperature (momentarily) | 95 °C |
| Max. operating pressure at 20 °C | 10 bar |
| Max. operating pressure at max. medium temperature | 10 bar |
| Wall roughness | 0.007 mm |
| Expansion coefficient | 0.026 mm/ (m.K) |
| Flexible | Yes |
| Suitable for surface mounting | No |
| Min. bending radius | 32 mm |
| Min. bending radius without tools | 80 mm |
| Pipe colour | Grey |
| With mantle pipe | No |
| Outer diameter mantle pipe | - |
| With heating cable | - |

Data sheet for item 73516400

| | |
|-------------------------------------|-----|
| Colour outer sheath | - |
| With thermal insulation | No |
| Shape of insulation | - |
| Thickness of thermal insulation | - |
| Lambda value | - |
| Colour of thermal insulation | - |
| Outer diameter thermal insulation | - |
| Outer width rectangular insulation | - |
| Outer height rectangular insulation | - |
| Capped | Yes |
| UV resistant | No |
| Water content | - |
| Halogen free | Yes |
| SVGW certified | - |
| DIN-CERTCO certificate | - |
| With approval for TÜV | - |
| DVGW quality mark for gas | - |
| DVGW quality mark for water | - |
| Compliant with NF 545 | - |
| KOMO certified | - |
| Type approval according to BBR/EKS | - |

