

# TP-200 STT Remote Temperature Button Sensor Probe

## Product overview




TP-200 is a multi use temperature bullet sensor to be used in conjunction with Whisper thermostats. The sensor can be used as a remote sensor to improve a room's temperature control, or as a floor sensor to help protect the under floor heating from becoming too hot.

- Slimline at only 5mm suitable for standard drill bit size holes.
- Suitable for wet room applications with anti corrosive stainless steel probe design.
- Long fixed cable lengths from 3m to 20m ensuring a solution for every need.
- Common NTC 10K  $\Omega$  resistance range for ease of stock control.
- High accuracy of 1% giving installer confidence.
- Standard range of 3950k B25/50.

## Technical specifications

Item	Remote room or floor sensor	Accuracy	+/-1%
Product code	See below	Colour	White
Dimensions	5 x 20mm probe*	Mounting type	In housing (RH-300) or oor in floor
Cable lengths	3m, 10m, 15m, 20m	Working temp	-40 to +120 °C
Cable material	Semi rigid PVC	Cable type	2 core multi-strand
Probe material	Stainless steel 304	Sensor type	NTC Thermistor 10K $\Omega$
		Resistance	10k Ohms at 25°C



## Sensor resistance table

Temperature	Resistance
-40	328.8
-30	172.9
-20	95.1
-10	54.4
0	32.2
10	19.7
20	12.4
25	10.0
30	8.0

Temperature	Resistance
40	5.3
50	3.6
60	2.5
70	1.7
80	1.2
90	0.9
100	0.7
110	0.5
120	0.3

Product code	Cable length
CWS-TRP1-230	3m
CWS-TRP1-231	10m
CWS-TRP1-232	15m
CWS-TRP1-233	20m



Whisper Controls Limited

Unit 21D Avenue Two, Station Lane Industrial Estate, Witney, Oxfordshire, OX28 4YG, United Kingdom.

Tel: +44 (0)1993 640073 [whispercontrols.com](http://whispercontrols.com)

DS-WC-TP-200-MAY24-V1.0