




**Geberit Duofix frame for wall-hung WC, H112, with Sigma cistern 12 cm (UP320)**

**Application purpose**

- For installation of a wall-hung WC with bolt fixings set at 180 or 230 mm centres
- For installation in a room-height Duofix system wall in front of a solid or drywall construction
- For mounting in front of a solid or drywall construction
- For a screed of 0 - 200 mm (not in room height applications)
- For connecting Geberit AquaClean
- Any boarding must be fixed tight up against the face of the Duofix frame and screwed directly to the frame.

**Characteristics**

- Self-supporting
- Frame with C profile 40/40 mm
- Powder-coated frame, ultramarine blue
- Galvanised leg supports, steplessly adjustable 0 - 200 mm
- Feet can be retracted 5 cm
- Rotating foot plate, for installation in UW50 and UW75 profiles
- Frame with holes  $\varnothing$  9 mm for fastening in wood frame construction
- Sound-absorbing actuator rods, tool-free, fast adjustment
- Easy to clean coating on glass and metal
- Concealed cistern fully insulated against condensation
- Concealed cistern for tool-free mounting and maintenance
- Frame height 1120 mm
- With wall brackets to allow up to a 200 mm duct. For larger ducts up to 400 mm use extension bolts 111.887.00.1
- Tool-free fastening for outlet bend, sound-absorbing, adjustable in depth with 8 positions, adjustable range 45 mm
- Connection hose to angle stop valve can be screwed without tools
- Water supply connection at centre back or at the top
- Geberit Sigma concealed cistern 12 cm (UP320) with front actuation
- Dual flush with Sigma80 touchless, Sigma60, Sigma50, Sigma20, Sigma10 touchless, Sigma01 or Bolero flush plates
- Single flush with Sigma10 or Tango flush plates
- Dual flush with pneumatic and mechanical buttons
- Single flush with touchless flush or pneumatic buttons
- The protection cover protects the service opening against moisture and dirt and can be mounted without tools and cut to length
- Universal water supply connection compatible with MeplaFix, can be mounted and operated without tools
- Self-locking feet for tool-free alignment of the frame, (friction feet have to be locked with spanner)
- For pans with contact surfaces smaller than 170 mm (see accessory 111.847.00.1)
- Flush valve features settings to enable either a 6l and 3l flush or a 4.5l and 3l flush. For flush volumes of 4l and 2l a low flush beaker is required (241.894.00.1)
- Note: must be used with pans designed for low volume flush.
- The cistern can be operated with used water (rainwater) provided it is passed through a filter system first.

## Technical data

Flow pressure range	0.1-10	bar
Operating temperature water max.	25	°C
Flush volume small range	3-4	l
Flush volume factory setting	5.8 and 3	l

## Scope of delivery

- 2 Duofix PreWall brackets for system
- Water supply connection R 1/2" male BSP parallel thread with integrated angle stop valve and hand wheel
- Conduit pipe for the water supply connection of Geberit AquaClean
- Flush bend
- Protection plug
- Protection housing for service opening
- 2 threaded rods M12 for ceramics fastening
- WC connection set,  $\varnothing$  90 mm
- WC outlet bend, HDPE,  $\varnothing$  90 mm
- Adaptor sleeve, HDPE,  $\varnothing$  90/110 mm
- Fastening material

Excluded:

- Flush plate

## Article

Article no.	PU1	PU4
<b>111.383.00.5</b>	1	12