



Geberit Sigma concealed cistern 12 cm, (UP320)



Application purpose

- For concealed installation
- For back to wall floor-standing WCs

Characteristics

- Concealed cistern fully insulated against condensation
- Front actuation only
- Protection cover for service opening can be mounted without tools and cut to length
- Dual flush with Sigma80 touchless, Sigma60, Sigma50, Sigma20, Sigma10 touchless, Sigma01 or Bolero flush plates
- Dual flush with pneumatic and mechanical buttons
- Single flush with Sigma10 or Tango flush plates
- Single flush with touchless flush or pneumatic buttons
- Water supply connection at centre back or at the top
- Flush bend has maximum 8 cm adjustment. Flush can be cut down by maximum of 8 cm
- Installation height 1080 mm (can be cut down, depending on the WC pan performance)
- Minimum install height 950 mm
- Fastening bracket adjustable in depth
- Cistern can be reversed to give access from behind in a duct situation when flushed with pneumatic buttons or touchless flush
- Flush valve features 6l and 4.5l flush settings to enable either a 6l and 3l flush or a 4.5l and 3l flush. For flush volumes of 4l and 2l a low flush beaker is required (241.894.00.1)
- The cistern can be operated with used water (rainwater) provided it is passed through a filter system first
- Note: must be used with pans designed for low volume flush.

Technical data

Flow pressure range	0.1-10	bar
Operating temperature water max.	25	°C
Flush volume small range	3-4	l
Flush volume factory setting	5.8 and 3	l

Scope of delivery

- Water supply connection R 1/2" male BSP parallel thread with integrated angle stop valve
- Protection housing for service opening
- Flush pipe ø 45 mm
- Fastening for flush bend
- Protection plug for flush pipe
- 2 slotted flat irons
- 2 fastening brackets, pre-mounted
- Fastening material

Excluded:

- Flush plate

Article

Article no.	PU1	PU4
109.309.00.5	1	24