

2500 Litre Bunded Fuel Storage and Dispensing Tank

FuelMaster 2500 litre bunded fuel storage and dispensing tank.
Suitable for agricultural or commercial applications such as storing and dispensing diesel for vehicles.



Specifications

Oil Level Monitor	WatchmanSonic fitted as standard
Capacity Ltr/Gal	2500/550
Length (mm)	2430
Width (mm)	1420
Height (mm)	1855
Guarantee Period	10 years (one year on components)
OFCERT No	0642069817
Pump Options	Rotary, 12 Volt, 110 Volt, 230 Volt
Hose Length (m)	4
Overfill Prevention	SpillStop device as standard
Fuel Type	Agricultural Fuel Oil (Class 2A) and Gas/Oil/Diesel (Class D) and Diesel Fuel in accordance with BS EN590
Regulation Compliance	The Control of Pollution Regulations and comparable requirements across the UK and Ireland
Equipment Options	Automatic Nozzle, Flow Meter, 10 Micron Partile Filter, Tank Monitoring System

Details

- The robust, ribbed construction protects against accidental damage and will not rot or rust, even in the most exposed locations.
- Non-gravity feed, along with access to a lockable cabinet to activate the integral pump, which dispenses at 56 litres per minute.
- They are guaranteed for 10 years (pump and accessories guaranteed for one year) and are storage tank of choice for safe storage of fuel.
- Available with a 10 micron particle and water filter
- Fitted with WatchmanSonic oil level monitor device but also has a more sophisticated Tank Monitoring System option. (TMS an optional extra). The TMS can remotely electronically monitor fuel levels in the tank displaying information back at a computer screen in an office. It can also be linked to existing management systems.
- Fitted with a overfill prevention device, SpillStop to prevent groundwater pollution.