Sentinel X300

System Cleaner for New Central Heating Systems

Features & Benefits

- · Removes oils, greases, flux residues etc.
- Prepares and protects metal surfaces
- Helps prevent radiator pin-holing
- Suitable for all metals including aluminium
- Non-acid, non-caustic
- No neutralisation procedure is needed
- Easy to handle
- Manufactured under a quality system conforming to ISO9001

Application

Sentinel X300 has been formulated as a cleansing aid for new central heating systems and those up to 6 months old. It will effectively remove excess flux residues, greases, oily contaminants, sludge and installation debris.

Sentinel X300 passivates the metal surfaces in the system and helps prevent copper deposition, which frequently causes severe pinhole corrosion in radiators.

Sentinel X300 is a neutral formulation that can be used in all types of indirect heating systems including those containing aluminium components.

Dosing & Feeding

1 litre of Sentinel X300 is sufficient to treat a typical domestic system of 8 to 10 radiator panels. Larger systems should be dosed with 2 litres. If the system is new, this should be at the time it is first filled. For best results, the water should be circulated at normal operating temperature for between 1-2 hours but no longer than 24 hours.

If it is not possible to heat the water, the circulation time must be compensated for by extending the time to at least 24 hours but no longer than one week.

Drain and flush the system before refilling and treating with Sentinel X100 inhibitor or Sentinel X500 inhibited antifreeze.

Open Systems: Dose via F&E cistern, via a by-pass feeder or use a Sentinel Dosing Vessel.

Sealed Systems: If the system is empty, add to any convenient point before filling. If full, use a Sentinel Dosing Vessel to inject via the filling loop or other access point.

Physical Properties

 Appearance: Slightly hazy colourless to pale yellow liquid

Odour: Mild

Specific gravity: 1.23 (20°C)
pH (concentrate): 7 (approx)
Freezing point: 0°C

Packaging

- 1 litre bottle
- 10 litre cubitainer
- 20 litre cubitainer

Safety Precautions

The information provided overleaf enables compliance with the Control of Substances Hazardous to Health Regulations. A full Safety Data Sheet is available upon request.

www.sentinel-solutions.net



Product Facts

Sentinel X300

| System Cleaner for Central Heating Systems | An aqueous solution of phosphate, organic heterocyclic compounds, polymers and organic bases. |
|---|--|
| Health Hazards | Not for use in potable water systems. |
| nealth nazarus | Not considered hazardous to health. |
| Landling | Avoid contact with akin and avoc |
| Handling | Avoid contact with skin and eyes. Keep out of reach of children and animals. Wash out empty container thoroughly with water before disposal. |
| Storage | Keep container tightly closed. Store in cool, well ventilated area. |
| Spillage | Flush spillage with plenty of water and wash to waste. |
| Fire/Explosion Risks | Non-flammable |
| First Aid | Skin Exposure: Wash immediately with plenty of water. If irritation develops, seek medical attention. Eye Exposure: Flush immediately with plenty of running water. Seek medical attention. |
| | Ingestion: Rinse mouth with water. Do NOT induce vomiting! Seek medical attention. |

