Product Data Sheet



bottom → 315 — + +90 6 50 715 fixing screws 190 outlet | 160 | 102 OD | 280 120 cealed brackets (supplied) fixing centres 280 **⊢210**− fixing screws - 525

Profile 21 Close Coupled WC Pan

Illustrated

S3092 Profile 21 WC pan close coupled with horizontal outlet S3094 Profile 21 close coupled cistern 4/2.6 litre dual flush push button valve, bottom supply and internal overflow

S4103 Profile 21 seat and cover

Configuration options

S3093 Profile 21 close coupled cistern, 6/4 litre dual flush push

button valve bottom supply and internal overflow

S4102 Profile 21 seat and cover, slow close

S4305 Panekta outlet Connector, finned pattern to convert

horizontal outlet WCs to P trap

S4300 Panekta outlet Connector, finned pattern to convert

horizontal outlet WCs to S or turned P trap

Material

Vitreous China Vitreous china to BS 3402

Weights

S3092 17.59KG 18.51KG S3094 S4103 2 80KG

Special Notes

Standards

WC screwed to floor & cistern screwed to wall.

Colours

White (01)

Frequently used applications

Education Factory General Healthcare Hotels Office **Public Building** Pubs and Clubs Residential Retail Sports and Leisure

Features

Water Saving

Accreditations

Water Label

WTL

.....



Tel: 0870 122 8822 Fax: 0870 122 8282 Email: info@idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Web: www.idealspec.co.uk

Idealspec

Date created:26/07/2013