



Doc M Sandringham Bowl Urinal

Illustrated

- S6103** Sandringham wall bowl urinal
- S6454** Contour 21 grab rail straight 60cm long x 35mm diameter
- S6215** Conceala auto cistern 4.5 litre with cover, auto syphon and petcock
- S8770** Waste 1½" strainer waste brass with stainless steel dome
- S8915** Trap 1½" plastic bottle with 75mm seal
- S6226** Flushpipes concealed for 1 bowl urinal
- S6265** Spreader, back inlet Sandringham

Configuration options

- S6200** Mura 4.5 litre auto cistern with auto syphon, petcock and supports
- S6210** Regal 4.5 litre auto cistern and cover, auto syphon and petcock
- S6220** Flushpipes exposed for 1 bowl urinal with Mura cistern
- S6266** Spreader top inlet Sandringham

Material

Vitreous China

Weights

- S6103 7.50KG
- S6454 2.00KG
- S6215 3.00KG
- S8770 0.16KG
- S8915 0.24KG
- S6226 0.41KG
- S6265 0.36KG

Colours

White (01)

Standards

Layout conforms to BS8300:2001 and Document M Overflow the Building Regulations.

Special Notes

Wheelchair users may be able to pull themselves to a standing position to use a urinal, or they may be able to use a urinal from their wheelchair. The lower urinal position shown is also beneficial to a person of lower stature. Must be used in wheelchair accessible male washrooms. Minimum of 2 x 600mm S6454 grab rails.

Frequently used applications

- | | |
|-----------------|--------------------|
| Education | Factory |
| Hotels | Office |
| Public Building | Pubs and Clubs |
| Retail | Sports and Leisure |

Features

- DocM
- Special Care
- Water Saving

*Armitage
Shanks*

Tel: 0870 122 8822
Fax: 0870 122 8282
Email: info@idealspec.co.uk
Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by
Ideal Spec

Date created: 26/07/2013