



Contour 21 Washbasin 50cm No Taphole No Chainstay Hole or Overflow - General Use

Illustrated

- S2154** Contour 21 back outlet washbasin, 50cm, no tapholes, no overflow, no chainstay hole
- A6060** Markwik 21 integral thermostat, single sequential lever bib mixer, single flow horizontal outlet, 2 x ½" inlets at 200mm centres, Armitage Bioguard outlet fitted
- S8750** Waste 1¼" outlet adaptor for all Contour back outlet washbasins
- S8920** Trap 1¼" plastic resealing bottle, 75mm seal
- S9112** Concealed hangers pressed Steel, toggle bolts and clips for Contour washbasins

Configuration options

- S8746** Plastic strainer for back outlet washbasins
- S7241** Avon bib tap, non concussive self closing
- S9006** Isolating valve ½" with screwdriver control, inlet for 15mm copper, outlet with ½" BSP female swivel capnut
- S9005** Volume Control valve ½" with screwdriver control, inlet and outlet for 15mm copper
- A5900** TMV Thermostatic mixing valve 15mm
- S8910** Trap 1¼" plastic bottle, 75mm seal

Material

Vitreous China

Standards

Vitreous china to BS 3402

Weights

S2154	12.84KG
A6060	4.00KG
S8750	0.17KG
S8920	2.00KG
S9112	0.47KG

Special Notes

Suggested rim heights; 780-800 for ambulant users 680-700 for wheelchair users. Washbasin wall mounted using S9112 hangers or panel mounted using S9112 hangers, toggle bolts & clips. Toggle bolts and outlet adaptor suitable for maximum panel thickness of

Colours

White (01)

Designer

Robin Levien, RDI

Frequently used applications

General Healthcare
Sports and Leisure

Hospitals

Armitage
Shanks

Tel: 0870 122 8822
Fax: 0870 122 8282
Email: info@idealspec.co.uk
Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by
Ideal Spec

Date created: 08/08/2013