



Contour HygenIQ Urinal Fully Concealed

Illustrated

- S6119** (UR H) Contour HygenIQ urinal 67cm, concealed
- S8849** HygenIQ plastic splash reducing waste, 50mm unslotted tail
- S8970** Trap 1½" plastic P with 75mm seal, multi-purpose outlet suitable for plastic and BS copper pipe
- S9275** Urinal concealed hangers, Steel
- S6286** Spreader, back inlet for vitreous china urinal
- S9276** Toggle bolts to suit maximum 25mm panel thickness

Configuration options

- S6215** Conceala auto cistern 4.5 litre with cover, auto syphon and petcock
- S6216** Conceala auto cistern 9.0 litre with cover, auto syphon and petcock
- S6217** Conceala auto cistern 13.6 litre with cover auto syphon and petcock
- S6226** Flushpipes concealed for 1 bowl urinal
- S6227** Flushpipes concealed for 2 bowl urinals
- S6228** Flushpipes concealed for 3 bowl urinals
- S6229** Flushpipes concealed for 4 bowl urinals
- S6230** Flushpipes concealed for 5 bowl urinals
- S6120** (UR H) Urinal division Vitreous China with hanger and screw
- S8147** Sensorflow Solo urinal control for panel mounting with integral proximity sensor

Material

Vitreous China

Standards

Vitreous china to BS 3402

Weights

S6119	18.50KG
S8849	1.70KG
S8970	1.00KG
S9275	1.00KG
S6286	0.31KG
S9276	2.00KG

Special Notes

Please click the [Specify this] button and then choose the number of bowls in each range. See further pages for additional information on flushpipes for ranges of from 1 to 5 urinals. See also Sensorflow urinal flushing page

Colours

White (01)

Frequently used applications

Education	Factory
Hospitals	Hotels
Office	Public Building
Pubs and Clubs	Retail
Sports and Leisure	Vandal Risk

Features

HTM
Water Saving

*Armitage
Shanks*

Tel: 0870 122 8822
Fax: 0870 122 8282
Email: info@idealspec.co.uk
Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by
Ideal Spec

Date created:02/07/2013