


Geberit Mapress Copper adaptor with male thread

**Application purpose**

- For technical building systems, industry and shipbuilding
- Application overview: Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54$ mm
- Seal ring made of CIIR, black, up to $\varnothing \leq 54$ mm
- Seal ring made of EPDM, black, from $\varnothing > 54$ mm
- Pressing socket with transparent protection plug

Technical data

Material

Gunmetal (CuSn5Zn5Pb2-C)

Article

Art. no.		DN	d, ø [mm]	R ["]	H [cm]	L [cm]
61701	N	10	12	3/8	1.5	3.2
61745	N	10 / 15	12	1/2	1.9	3.6
61702		12 / 10	15	3/8	1.3	3.3
61703		12 / 15	15	1/2	1.6	3.6
61714		12 / 20	15	3/4	1.8	3.8
61704		15	18	1/2	1.7	3.7
61705		15 / 20	18	3/4	1.8	3.8
61715		20 / 15	22	1/2	1.7	3.8
61707		20	22	3/4	1.8	3.9
61716		20 / 25	22	1	2	4.1
61717		25 / 20	28	3/4	1.9	4.2
61708		25	28	1	2	4.3
61718		25 / 32	28	1 1/4	2.1	4.4
61719		32 / 25	35	1	2.2	4.8
61709		32	35	1 1/4	2.3	4.9
61721		40 / 32	42	1 1/4	2.8	5.8
61710		40	42	1 1/2	2.8	5.8
61711		50	54	2	2.8	6.3
61730		65	66.7	2 1/2	4.7	9.7
61732		65	76.1	2 1/2	4.8	10.1
61733		65	76.1	3	5.3	10.6
61734		80	88.9	3	5	11

 N: New, available as of April 2016