## Atkinson SIGHT-GAUGES

These gauges give a clear reading of the level of contents in a tank. They have unbreakable sight tubes and can be supplied in lengths to suit any depth tank.

Push Button Gauge Specifications:		Push Button Gauge Type PBG - This unit is fitted with a self closing valve designed to comply with BS 799 and OFTEC OFS E103 has been accepted by major oil companies.	
Approvals	- BS 799 Pt.2. OFTEC, OFS E103.		
Тор Сар	- Protection against insects and dust.	Line of Tank	
Top Clip	- To provide upper support for the sight tube. Supplied with self tapping fixing screws.		
Sight Tube	- Clear PVC.		2
Sight Tube Shield	- Rigid PVC. (or Aluminium if requested).	3 8 2	
Coupler	<ul> <li>A push fit onto the sight tube shield to cover the valve nipple.</li> </ul>	OIL FIRING TECHNICAL ASSOCIATION FOR THE PETROLEUM INDUSTRY	
Operation	- Push button to indicate oil level.		
Tank Connection	- Union complete with locknut.		
Union Size	- ½" BSP standard. ¾" BSP or 1" BSP also available.	OIL FIRING EQUIPMENT GROUP MEMBER	
Gauge Length	- To suit tank depth.	A control valve should always	
Application	- Heating Oil, Diesel Oil, Paraffin etc.	be fitted at the outlet first, (control valve not supplied	
Dimension		with the gauge).	
Length	- 4' 0" (122.0 cm.). 5' 0" (152.5 cm.). 6' 0" (183.0 cm.). All Standard.	Ţ	I P
Weight	- Approx. 0.75 Kg.		

Atkinson Equipment Limited, West Wilts Trading Estate, Westbury, Wiltshire. BA13 4JF.
Telephone: (01373) 822220/823170 Facsimile: (01373) 826996

Shown approximately half size.