

Atkinson

TANKMASTER

Tankmaster

Specifications:

Designed to comply with BS799 Pt 2

Application -

For fitting to steel or plastic oil heating storage tanks. (Note a range of adaptors is available for plastic tanks).

For use with oil central heating systems. Eliminates the need for a separate gate valve, level gauge, filter, fire valve and a number of pipe fittings.

Oil Take Off -

Either right hand or left hand.

Gauge Length -

To suit tank depth.

Sight Tube -

Clear P.V.C.

Sight Tube Shield -

Rigid P.V.C.

(Aluminium by request).

Sight Tube Assembly -

Detachable.

Oil Level Valve -

Pull to read (Self Closing).

Fire Valve -

Automatic over temp. shut off.

Oil Line Outlet -

10mm copper compression.

Oil Flow Rate -

Up to 36 litres per hour (8 gallons per hour).

Tank Connection -

1/2" BSP.

Filter -

Replaceable when boiler is serviced. NOT washable.

Construction:

Body -

Die-cast zinc alloy.

Filter Bowl -

Plated Steel.

Dimensions:

Body Assembly -

15.5cm x 8cm.

Sight Tube Assembly -

As required.

Total Weight (4" 0") -

1.0 kg (approx.).



Four-in-One Level Gauge

- Sight Gauge
- Shut off Valve
- Fire Valve
- Disposable Filter
- Right or Left Hand Compression fitting

All to BS799
OFTEC OFS E103

Filter Bowl Detail



Plated steel bowl with bolt fixing to discourage vandalism.



Atkinson Equipment Limited, West Wilts Trading Estate, Westbury, Wiltshire. BA13 4JF.
Telephone: (01373) 822220/823170 Facsimile: (01373) 826996