



Never compromise on quality!



SAVES NAILS

Multi-purpose Rubber Based Adhesive

Description

A multi-purpose, rubber based construction adhesive in mild solvents, that can replace mechanical fixings in a wide variety of domestic, commercial and industrial applications.

SAVES NAILS is a fast bonding adhesive with gap-filling properties to bridge gaps up to 12mm. It can be used in all weather conditions and is suitable for rough and porous surfaces. It has good low temperature resistance for freezers and cold applications. This product is toluene free.

Uses

Bond It **SAVES NAILS** is ideal for fixing a wide variety of materials to all types of walls and suitable for insulating PU foams. It can also be used to fix skirting boards, door surrounds and frames, window sills, all types of cladding, wall battens, decorative wall boards, metal carpet edges, automotive trims and much more. It can be used for interior and exterior applications.

SAVES NAILS is ideal for use on:

- ◆ brick
- ◆ timber
- ◆ stone
- ◆ concrete
- ◆ ceramic
- ◆ some plastics
- ◆ marble
- ◆ brick veneer
- ◆ metal

Preparation

Ensure all surfaces are clean, dry and free from grease or any contaminants that may hinder adhesion.

Application

Apply using a standard sealant gun with the nozzle cut at an angle of 45°, and to an opening slightly larger than the joint to be sealed. Apply a 6mm bead (or thicker to suit gap) in a zig zag along one length of the item to be fixed. Press into place and apply an even pressure on the entire surface, leave to cure for 48 hours. Temporary support or fixings are recommended on very heavy items whilst curing.

Bracing or additional mechanical fastening is

recommended for ceiling or heavy wall panels while the adhesive develops full strength. When bonding foam to ceiling additional mechanical fastenings are to be used. Excessive material can be removed using white spirit or cellulose thinners. Clean tools immediately after use.

Limitations

- Not suitable for areas subject to frequent water immersion.
- Not recommended for use on asphalt, bitumen or polystyrene.
- Not to be used as a mirror adhesive.
- Dusty or porous surfaces should be primed with a primer prior to application - consult our technical department for details.

Container Size

EU3 polyamide cartridge.

Storage Conditions

Store in cool, dry conditions below 30°C. Keep containers in a well ventilated area. Must be stored in accordance with flammable liquid storage regulations.

Shelf Life

Use within 12 months.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

In the event of spillage remove all sources of ignition, ventilate the area, remove people from confined areas. Material should be mopped up immediately with an inert absorbent material such as sand or sawdust and scooped up with non-sparking tools.

Health & Safety

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Avoid breathing vapours. Use only in a well ventilated area. Wear protective gloves and eye protection. If on skin (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/ shower. If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell. Store in a well ventilated place. Keep cool. Store locked up. Keep out of reach of children.

MSDS sheets available for professional user on request. All details can be downloaded from www.bond-it.co.uk. Always follow manufacturers recommendations when using this product.

Specification Summary

| | |
|----------------|--|
| Flammability | Highly flammable |
| Full Cure Time | 48 hours depending on bead thickness and temperature |

Container Sizes:

| | |
|----------|---------------|
| Code: | BDSN2 |
| Size: | EU3 |
| Qty: | 25 |
| Barcode: | 5060021361615 |

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V3 03/09/14
Supersedes V2 13/12/14