


Geberit Mapress Copper T-piece, reduced

**Application purpose**

- For technical building systems, industry and shipbuilding
- Application overview: Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54$ mm
- Seal ring made of CIIR, black, up to $\varnothing \leq 54$ mm
- Seal ring made of EPDM, black, from $\varnothing > 54$ mm
- Pressing socket with transparent protection plug

Technical data

Material

Cu-DHP copper CW024A
(EN 1412)

Article

Art. no.	DN	d, ø [mm]	d1, ø [mm]	d2, ø [mm]	L [cm]	L1 [cm]	l [cm]	l2 [cm]	Z [cm]	Z1 [cm]	Z2 [cm]
61243	12 / 10 / 10	15	12	12	6.7	3.3	3.2	3.5	2	1.6	1.7
61252	12 / 10 / 12	15	12	15	6.4	3.3	3.2	3.2	1.2	1.6	1.2
61104	12 / 20 / 12	15	22	15	7.4	3.4	3.7	3.7	1.7	1.3	1.7
61253	15 / 10 / 15	18	12	18	6.8	3.5	3.4	3.4	1.4	1.8	1.4
61235	15 / 12 / 12	18	15	15	7.4	3.5	3.4	4	1.4	1.5	2
61254	15 / 12 / 15	18	15	18	6.8	3.5	3.4	3.4	1.4	1.5	1.4
61236	15 / 15 / 12	18	18	15	7.4	3.4	3.4	4	1.4	1.4	2
61244	20 / 10 / 20	22	12	22	7.4	3.5	3.7	3.7	2.1	1.7	2.1
61240	20 / 12 / 12	22	15	15	8	3.8	3.7	4.3	1.6	1.8	2.3
61256	20 / 12 / 20	22	15	22	7.4	3.8	3.7	3.7	1.6	1.8	1.6
61257	20 / 15 / 20	22	18	22	7.4	3.8	3.7	3.7	1.6	1.8	1.6
61242	20 / 20 / 12	22	22	15	7.4	3.7	3.7	4.5	1.6	1.6	2.5
61259	25 / 12 / 25	28	15	28	8.4	4.1	4.2	4.2	1.9	2.1	1.9
61260	25 / 15 / 25	28	18	28	8.4	4.1	4.2	4.2	1.9	2.1	1.9
61261	25 / 20 / 25	28	22	28	8.4	4.1	4.2	4.2	1.9	2	1.9
61212	32 / 12 / 32	35	15	35	10	5.1	5	5	2.4	3.1	2.4
61213	32 / 15 / 32	35	18	35	10	5	5	5	2.4	3	2.4
61214	32 / 20 / 32	35	22	35	10	5.2	5	5	2.4	3.1	2.4
61215	32 / 25 / 32	35	28	35	10	5.5	5	5	2.4	3.2	2.4
61229	40 / 12 / 40	42	15	42	11.4	5.4	5.7	5.7	2.7	3.4	2.7
61217	40 / 15 / 40	42	18	42	11.4	5.4	5.7	5.7	2.7	3.4	2.7
61218	40 / 20 / 40	42	22	42	11.4	5.5	5.7	5.7	2.7	3.4	2.7
61219	40 / 25 / 40	42	28	42	11.4	5.8	5.7	5.7	2.7	3.5	2.7
61220	40 / 32 / 40	42	35	42	11.4	6.2	5.7	5.7	2.7	3.6	2.7
61227	50 / 20 / 50	54	22	54	13.8	6.1	6.9	6.9	3.4	4	3.4

61228	50 / 25 / 50	54	28	54	13.8	6.4	6.9	6.9	3.4	4.1	3.4
61225	50 / 32 / 50	54	35	54	13.8	6.8	6.9	6.9	3.4	4.2	3.4
61226	50 / 40 / 50	54	42	54	13.8	7.2	6.9	6.9	3.4	4.2	3.4
61280	65 / 20 / 65	66.7	22	66.7	22	6.5	11	11	6	4.4	6
61281	65 / 25 / 65	66.7	28	66.7	22	6.8	11	11	6	4.5	6
61282	65 / 50 / 65	66.7	54	66.7	22	8.2	11	11	6	4.7	6
61283	65 / 20 / 65	76.1	22	76.1	23	7	11.5	11.5	6.2	4.9	6.2
61284	65 / 32 / 65	76.1	35	76.1	23	7.7	11.5	11.5	6.2	5.1	6.2
61285	65 / 40 / 65	76.1	42	76.1	23	8.1	11.5	11.5	6.2	5.1	6.2
61286	65 / 50 / 65	76.1	54	76.1	23	8.7	11.5	11.5	6.2	5.2	6.2
61287	65 / 65 / 65	76.1	66.7	76.1	23	10.8	11.5	11.5	6.2	5.8	6.2
61288	80 / 20 / 80	88.9	22	88.9	26	7.6	13	13	7	5.5	7
61289	80 / 40 / 80	88.9	42	88.9	26	8.7	13	13	7	5.7	7
61290	80 / 50 / 80	88.9	54	88.9	26	9.3	13	13	7	5.8	7
61292	80 / 65 / 80	88.9	76.1	88.9	26	11.4	13	13	7	6.1	7
61293	100 / 20 / 100	108	22	108	31	8.6	15.5	15.5	8	6.5	8
61294	100 / 50 / 100	108	54	108	31	10.3	15.5	15.5	8	6.8	8
61295	100 / 65 / 100	108	66.7	108	31	12.4	15.5	15.5	8	7.4	8
61296	100 / 65 / 100	108	76.1	108	31	12.4	15.5	15.5	8	7.1	8
61297	100 / 80 / 100	108	88.9	108	31	13.5	15.5	15.5	8	7.5	8