


FRENZY

Thermostatic Cool Touch Bar Shower Valve Only with Fast Fit Connections

Product Specification

Product Code:	FZ SHXVOCTFF C
Finish:	Chrome
Product Type:	Contemporary
Construction:	Body is of brass construction
Valve Type:	¼ Turn ½" ceramic disc valve
Cartridge Type:	Thermostatic Cartridge
Supply:	Suitable for all plumbing systems (Preferably balanced)
Inlet Connections:	15mm compression connections
Outlet Connection:	G ½
Working Pressures:	Min 0.2bar, Max 5.0bar
Dimensions for Fitting:	150mm inlet centres



Additional Information

- Unique Cool Chrome technology ensures the bar valve stays cool to the touch while in use.
- Dual control – Flow and temperature are controlled separately, giving accurate control of both
- Thermostatic cartridge maintains showering temperature to +/- 1°C by compensating for changes in the incoming water temperature and pressure giving the stable outlet temperature
- Factory set to a maximum of 38°C to eliminate the ability to select an unsafe temperature – this is adjustable to suit user preference up to a maximum of 46°C.
- Flow control handle incorporates an eco button to save water, this can be overridden by the user.
- Supplied with WMNT10 C fast fit connections.
- Chrome plated to BS EN 248

Flow Rates (litres per minute)


System Pressure (bar)	0.2	0.5	1.0	2.0	3.0	5.0
Open Outlet (Valve Fully Open)	4.2	7.5	11.2	15.8	19.4	25.0
Open Outlet (Eco Stop Position)	1.8	3.7	5.5	8.1	10.2	13.5

Compliance/Approvals

WRAS Certificate No: 1404021

Technical Advice: For further information please call 0844 7016273 or email customer@bristan.com

Guarantee: 5 years covering manufacturing faults.



Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG
Telephone: 0844 701 6274 Facsimile: 0844 701 6275
Web Site: www.bristan.com Email: enquire@bristan.com

