

Adoptable Inspection Chamber Systems

Marley have introduced a new adoptable inspection chamber range compliant with Sewers for Adoption and Building Regulations.




Compatible systems for pipe & fitting connections: 110mm solid wall drainage & 150mm Quantum sewer structured wall drainage.

All products in the Sewers for Adoption range are suitable for both adoptable and non-adoptable applications.

 CAD drawing available for download from marleypd.co.uk
 Kitemark certified product  BBA certified product
 Adoptable

315mm inspection chamber

Suitable for up to 2m in depth

	Size	Colour	Code
DUCTILE IRON LID AND CAST IRON FRAME			
	300 12.5 tonnes	Black	UCL315
CHAMBER RISER			
	300 500mm long. Includes 300mm seal	Orange	UAR2
	300 1m long. Includes 300mm seal	Orange	UAR3
INSPECTION CHAMBER BASE			
	315 Supplied with 4 blanking plugs. Max invert depth 2m (when used with UAR2/3 riser). 290mm high All 110mm connections	Black	UCC315

450mm inspection chamber

Suitable for up to 3m in depth

	Size	Colour	Code
DUCTILE IRON LID AND CAST IRON FRAME			
	450 12.5 tonnes	Black	UCL125
REDUCED ACCESS RING			
	For use with UCL125	Black	UCLRR2
DEEP INSPECTION CHAMBER RISER			
	450 For use with UCC3D or UCC5 when invert depth is greater than 1.2m. Max invert depth 3m (for SFA). 480mm high. Includes one 450mm seal	Black	UCR3
INSPECTION CHAMBER BASE			
	450 Max invert depth 3m (when used with UCR3) All socket connections. 400mm high 160 and 110mm connections	Black	UCC5
DEEP INSPECTION CHAMBER RISER CLIP			
	For use with UCR3 riser		UCC10D
INSPECTION CHAMBER INSERTS			
	Left hand	Black	UCB1
	Right hand	Black	UCB2
SPARE BLANKING PLUG			
	110 160 For use with UCC5	Black Black	UCP1 UCP2
SPARE RING SEAL			
	450 For use with UCR3	Black	SR450