





Share

We would love to see your new boiler and heating system.

-  @HeatingYourHome
-  Worcester Bosch UK
-  @WorcesterBosch
-  Worcester Bosch



DISCOVER THE GREENSTAR LIFE RANGE



Worcester Bosch

Cotswold Way
Warndon
Worcester
WR4 9SW

worcester-bosch.co.uk

Calls to and from Bosch Thermotechnology Ltd may be recorded for training and quality assurance purposes. Worcester Bosch is a brand name of Bosch Thermotechnology Ltd. This brochure is accurate at the date of printing, but may be superseded and should be disregarded if specification and/or appearances are changed in the interest of continued improvement. The statutory rights of the consumer are not affected.



Part No. 8 716 119 855
Issue A 05/19



By Appointment to
Her Majesty The Queen
Boiler Manufacturer
Worcester, Bosch Group
T/A Bosch Thermotechnology Ltd.
Worcester

The Worcester logo, featuring a stylized wave icon to the left of the word "WORCESTER" in a bold, black, sans-serif font.



DESIGNED FOR MODERN LIFE

After 50 years of award winning innovation, our new Greenstar Life range makes looking after the heating and hot water in your home easy. It not only features a modern new design but it's also part of our most powerful wall hung combi-boiler range, with increased power outputs of up to 50kW.



GIVING YOU MORE CONTROL

It's the little touches that make all the difference, so we've upgraded the controls and connectivity throughout the Life range. We have improved the boiler's display screen and created easier-to-use push control buttons, whilst making the Life range wirelessly compatible with the Bosch EasyControl, meaning you have the power to control your heating and hot water wherever you are. All of these changes have been made to make your life easier, and improve your comfort.



INTELLIGENTLY WORKING TO MAKE YOUR LIFE EASIER

Life also features innovative new technology designed to keep your system pressure at its optimum level. Our unique optional Intelligent Filling System constantly monitors your boiler's pressure and will automatically adjust if needed. This removes the need to manually top-up the system pressure. This keeps your boiler working at its best when you need it most.



QUIETLY WARMING YOUR HOME

The Life is the direct replacement for our multi award winning Greenstar CDi Classic. It has been redesigned, modernised and re-engineered to improve performance and maximise efficiency. It is also one of our quietest boilers yet, so you will never know it's there. For extra peace of mind we are also offering up to a **10 year guarantee*** on the Life range.



*Terms and conditions apply.



CONTROLS

The Greenstar Life range is compatible with a range of controls, offering you simple solutions to manage the heating and hot water to suit your home.



WIRELESS BOSCH EASYCONTROL

The wireless Bosch EasyControl is a smart internet-connected room thermostat that connects directly to your smartphone. It allows you to control your heating and hot water on-the-go.

GREENSTAR COMFORT + RANGE

The Greenstar Comfort is an intelligent programmer and a room thermostat allowing access to control functions from a single, easily accessible location.

THE BOILER, BUT NOT AS YOU KNOW IT

TECHNICAL SPECIFICATIONS

STYLE	Combi and Regular					System	
	3 0 k W	3 5 k W	4 0 k W	4 5 k W	5 0 k W	3 0 k W	3 5 k W
Maximum horizontal flue lengths (60/100)	17m	10m	11m	8m	9m	17m	10m
Maximum vertical flue lengths (60/100)	21m	14m	15m	12m	15m	21m	14m
Clearance above flue	170/210mm*	170/210mm*	170/210mm*	170/210mm*	170/210mm*	170/210mm*	170/210mm*
Clearance (sides)	5mm	5mm	5mm	5mm	5mm	5mm	5mm
Clearance (below)	200mm	200mm	200mm	200mm	200mm	200mm	200mm
Clearance (front)	600mm**	600mm**	600mm**	600mm**	600mm**	600mm**	600mm**
Width	440mm	440mm	440mm	440mm	440mm	440mm	440mm
Height	780mm	780mm	780mm	780mm	780mm	780mm	780mm
Depth	365mm	365mm	365mm	365mm	365mm	365mm	365mm
Flow rate at the hot water tap (35°C)	12.3 l/min [^]	14.3 l/min [^]	16.4 l/min [^]	18.3 l/min [^]	20.3 l/min [^]		
Flow rate at the hot water tap (40°C)	10.7 l/min [#]	12.5 l/min [#]	14.3 l/min [#]	16.1 l/min [#]	17.9 l/min [#]		
Output kW to central heating	3kW – 30kW	3.5kW – 35kW	3.5kW – 35kW	3.5kW – 35kW	3.5kW – 35kW		

* Height for either 60/100 flue or 80/125 flue.

** 20mm from a removable cupboard door. 600mm from a fixed surface for servicing. Same clearances for ventilated and unventilated compartments.

[^] Values for industry comparisons.

[#] Designed operational flow rate. Maximum flow rates will only be achieved if sufficient dynamic pressure is available. Maximum flow is subject to a tolerance of 15%. Refer to installation manuals for more information.