

## Underground Drainage Systems 110mm Pipe and Fittings





## 110MM PIPE & FITTINGS BS 4660:2000, BS EN 1401-1:2009, BS EN 124:1994, BS EN 13598 - 1:2010

- FloPlast socketed underground pipe incorporates the latest blown end technology. The easy fit rubber seal is held in place via a circular plastic insert allowing a retention of the seal in transit and a perfect connection for jointing.
- All Push-Fit underground fittings have a captive seal and snap cap which are designed to be user-friendly - no sharp edges, and with space restrictions in mind, allow for an easy fit connection. The seal is double ribbed, and the sockets incorporate a recessed area to provide space for the rubber seal to locate as the pipe is inserted, forming a high-capacity pressure point.

Manufacturers that produce to these standards: BS EN 1401:2009 / BS 4660:2000 BS 7158:2001 / BS EN 124:1994	110mm	160mm
Hepworth	1	1
Brett Martin	1	1
Osma/Wavin	1	1
Polypipe	1	1
Polypipe Terrain	1	1
Marley	1	1
Hunter	1	1

#### FloPlast Installation Videos

Our step-by-step installation videos (available online), make it clearer and easier to get to grips with the

all the technical elements involved in what may be a complex process.

Visit www.floplast.co.uk and download a pdf step by step guide to help with your installation.



, , , , , , , , , , , , , , , , , , , ,			
Product		Code	
Pipe		Code	
Tipe			
	Plain Ended 3m		
	(Bale quantity 50) 6m	D046	
	2	D1 40	
	Single Socket 3m (Bale quantity 50) 6m		
	(sale domining 20) Om	D146	
Pipe Couplin	g		
Car Is	Single Socket Coupling	D124	
	Double Socket Coupling		
	Removable centre stop for use as slip coupling	D105	
Single Socke	t Bends		
	871/2° Bend (Socket/Spigot)	D161	
	45° Bend (Socket/Spigot)	D163	
	30° Bend (Socket/Spigot)	D164	
	15° Bend (Socket/Spigot)	D167	
Double Socke	et Bends		
	871/2° Bend	D561	
Marie Contraction of the Contrac	45° Bend	D563	
	30° Bend	D564	
	15° Bend	D567	
	87½° Rest Bend	D571	
	87½° Settlement Rest bend	D570	
10	67 72 Selliellielli Kesi belid	D370	
	0-90° Adjustable Bend	D560	
	(PP-Do not solvent weld)		
110mm non-return valve			
1	(6		
	110mm Non-Return Valve-Single Flap	D550	
	Tarre origin Flap		
Large Radius Bends			
	871/2° Plain End	D281	
	45° Plain End	D283	
	871/2° PE with Channel Access	D581	
	45° PE with Channel Access	D583	

2 Underground Systems www.floplast.co.uk

## 110MM PIPE & FITTINGS BS 4660:2000, BS EN 1401-1:2009, BS EN 124:1994, BS 7158:2001







Product		Code
Equal Junctions		
	87 <sup>1/20</sup> Junction (Double Socket) 45° Junction (Double Socket)	D190 D210
	$871/2^{\circ}$ Junction (Triple Socket) $45^{\circ}$ Junction (Triple Socket)	D191 D211
Access Fittin	gs	
	87½° Access Bend (Socket/spigot)	D169
8	Access Pipe (Socket/spigot)	D274
	Screwed Access Cap (Spigot)	D292
	Channel Access Pipe PE 1.5m	D870
Rodding Poi	nts	
	PCV Oval Rodding Point (Spigot)	D881
	PCV Oval Rodding Point (Socketed)	D882
	PCV Square Rodding Point (Spigot)	D883
	PCV Square Rodding Point (Socketed)	D884

Product		Code
Universal Tro	ips	
	Universal Gully Trap (Socket/Spigot 45°)	D500
T	Low Back 'P' Trap	D501
	Leaf/Debris Interceptor Gully (Black)	D94
	Spare Square Grid (Polypropylene)	D502
Universal Tro	ips	
	Square Blank Cover Grid	D508
	Square Hopper Including Polypropylene Grid	D504
	Rectangle Blank Cover Grid	D507
7	Rectangular Hopper (Including Polypropylene Grid)	D506



(45 rodding point with sealed access cover suitable for loading up to 10kN (1 tonne) where the frame of the cover is supported by a concrete plinth)

#### DrainGuard

Fits round and square downpipe (Black)	DG1
(Black)	DOI

www.floplast.co.uk Underground Systems 3



## 110MM PIPE & FITTINGS BS 4660:2000, BS EN 1401-1:2009, BS EN 124:1994, BS EN 13598 - 1:2010

Product		Code
Bottle Gully	Traps	
	Bottle Gully Circular Grid	D510
	NEW Bottle Gully Square Grid	D515
	Bottle Gully Rectangular Grid	D520
	Back Inlet Bottle Gully Rectangular Grid	D530
	Back Inlet Bottle Gully Circular Grid	D540
	Round Hopper and Grid (215mm diameter with height adjustment of 32mm)	D514
	NEW Square Hopper and Grid (216x216mm with height adjustment of 32mm)	D518
	Rectangular Hopper and Grid (295x216mm with height adjustment of 32mm)	D524
	200mm Riser	D505
Adaptors		
	110x50mm Waste Adaptor (Grey/Black/White)	SP95
	110x68mm Rainwater Adaptor (Grey/Black/White)	SP96
	Universal Waste Adaptor (32/40/50mm)	D95
	Universal Rainwater Adaptor (Square/Round)	D96
	80x110mm Adaptor	D97
	160×110mm Level Invert (Socket/Spigot)	D99
	Supersleve Clay Adaptor DS (Black) Hepsleve Clay Adaptor DS (Black)	D100 D101

#### **Features & Benefits**

- Provides an efficient means of waste water drainage and foul discharge from above ground drainage systems.
- Manufactured in PVC-U to give a strong durable product, lightweight and easy to work with and suitable for high temperatures and waste discharge.
- Fittings have an aesthetic modern look, are compact in size yet remain within the British Standard specification.
- Push-Fit joint through an innovatively designed seal and snap cap system.
- Comprehensive range of fittings to suit most installations and which integrate with all FloPlast above and below ground drainage systems.
- Colours available: Terracotta.

Colours available: Terracoffa.			
Product		Code	
Drain Conne	Drain Connector		
	(Black/Grey only)	SP107	
Connects directly in plastic pipe.	to socket of a cast iron clay or plastic pipe system to provide a so	cket for	
Flexible Cou	plings, Connectors and Adaptors		
	Flexi-Coupling 98mm-115mm	D102	
1 A A A	Flexi-Adaptor A: 98mm-115mm B: 120mm-136mm	D103	
Socket Plug			
•		D296	

Underground Systems www.floplast.co.uk

## 110MM PIPE & FITTINGS BS 4660:2000, BS EN 1401-1:2009, BS EN 124:1994, BS 7158:2001



Product		Code
Mini Access	Chamber - 300 Diameter (MAC)	
	270mm Deep Multi Inlet Chamber Base - 5x110mm flexible inlets / Supplied with 4 socket plugs (Allows for 0-20° of movement)	D800
	270mm 45° Inlet Chamber Base - 3x110mm flexible inlets / Supplied with 2 socket plugs (Allows for 0-20° of movement)	D801
	270mm 90° Inlet Chamber Base - 3x110mm flexible inlets / Supplied with 2 socket plugs (Allows for 0-20° of movement)	D802
	270mm 45° Inlet Chamber Base - 3x110mm Fixed inlets / Supplied with 2 socket plugs	D810
	100mm Chamber Riser With integral rubber ring (60mm cut down facility)	D820
	200mm Chamber Riser With integral rubber ring (60/100/150mm cut down facility)	D822
	340mm Sealed Screw Down Cover and Frame (35kN)	D830
	Block Paving Cover 300mm Square/Round	D932

www.floplast.co.uk Underground Systems 5

<sup>\*</sup>To conform with new document H Building Regulations H2000 use D930 or D931 as required.

# **FloPlast** building the future

FloPlast Limited
Castle Road
Eurolink Business Park
Sittingbourne
Kent ME10 3FP
UK

Tel: 01795 431731

Sales Office Direct Line: 01795 421422

Fax:

01795 431188

E-mail: sales@floplast.co.uk

Website: www.floplast.co.uk



#### Other systems available:













































