


Geberit Mapress Copper bend (gas)



Example image



Application purposes

- For natural gases
- For liquefied gases
- For natural and liquefied gases

- Leaky if unpressed
- Marked in yellow
- Seal ring made of HNBR, yellow
- Pressing socket with yellow protection plug

Characteristics

- Pressing indicator

Technical data

Material | Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, ø	arc	L	Z
34514	12	15 mm	45 °	3.6 cm	1.6 cm
34500	12	15 mm	90 °	3.8 cm	1.8 cm
34515	15	18 mm	45 °	2.9 cm	0.9 cm
34501	15	18 mm	90 °	4.2 cm	2.2 cm
34516	20	22 mm	45 °	3.2 cm	1.1 cm
34502	20	22 mm	90 °	4.7 cm	2.6 cm
34517	25	28 mm	45 °	3.7 cm	1.4 cm
34503	25	28 mm	90 °	5.7 cm	3.4 cm
34518	32	35 mm	45 °	4 cm	1.4 cm
34504	32	35 mm	90 °	6.5 cm	3.9 cm
34519	40	42 mm	45 °	4.7 cm	1.7 cm
34505	40	42 mm	90 °	7.6 cm	4.6 cm
34520	50	54 mm	45 °	5.7 cm	2.2 cm
34506	50	54 mm	90 °	9.5 cm	6 cm



- In 2020, the dimensions of bend d15/45° will be modified. The new dimensions are listed in the overview "Dimensional changes for Geberit Mapress Copper 2020".