


## Geberit Mapress Copper adaptor union with male thread



Example image



### Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water ≤ 120 °C
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

### Characteristics

- Pressing indicator
- Leaky if unpressed
- Union nut made of brass
- Seal ring made of CIIR, black
- Flat gasket made of EPDM
- Pressing socket with transparent protection plug

### Technical data

Media temperature with flat gasket EPDM	0–100 °C
Material	Gunmetal (CuSn5Zn5Pb2-C)

Art. no.	DN	d, ø	R	G	L	H
65531	10	12 mm	3/8 "	1/2 "	5.1 cm	3.4 cm
65540	10 / 15	12 mm	1/2 "	1/2 "	5.5 cm	3.8 cm
65532	12 / 15	15 mm	1/2 "	3/4 "	6.1 cm	4.1 cm
65541	12 / 20	15 mm	3/4 "	3/4 "	6.3 cm	4.3 cm
65533	15	18 mm	1/2 "	3/4 "	6.1 cm	4.1 cm
65542	15 / 20	18 mm	3/4 "	3/4 "	6.3 cm	4.3 cm
65534	20 / 15	22 mm	1/2 "	1 "	6.7 cm	4.6 cm
65543	20	22 mm	3/4 "	1 "	6.8 cm	4.7 cm
65544	20 / 25	22 mm	1 "	1 "	6.9 cm	4.8 cm
65535	25	28 mm	1 "	1 1/4 "	7.5 cm	5.2 cm
65536	32	35 mm	1 1/4 "	1 1/2 "	8 cm	5.4 cm
65537	40	42 mm	1 1/2 "	1 3/4 "	8.5 cm	5.5 cm
65538	50	54 mm	2 "	2 3/8 "	9.7 cm	6.2 cm