

Kingspan Ferham Specification sheet Open top cisterns - Oval

Features

- Application - Storage and supply of cold potable water to an open vented cylinder, or use as expansion tanks in vented heating systems
- Roto-moulded from approved hygienic polypropylene plastic
- Manufactured to BS4213:2004
- Kitemarked Certificat No. KM35963
- WRAS Certificat No. 1604081
- Supplied with close fitting lid, 22mm Byelaw 30 fittings, backing plate, 60mm insulation jacket and ties
- 1-Year Guarantee against manufacturing defects



Capacity		Height (mm)	Width (mm)	Depth (mm)	Code CISTERN
G	L				
15	68	380	860	508	FC15G
25	114	515	860	508	FC25G
40	182	440	1265	670	FC40G
50	227	525	1265	670	FC50G

Note: As Kingspan maintains a policy of ongoing continuous improvement, these specifications are subject to change without notice.

GB Sales Office:
T. 0345 260 0258
E. cylinder.sales@kingspan.com

Technical Support:
T. 0345 260 0007
E. cylinder.tech-support@kingspan.com

Wakefield Office:
Kingspan Water & Energy Ltd.
Tadman Street, Wakefield,
West Yorkshire, WF1 5QU

NI Sales Office:
T: 028 3836 4520
E: cylindersinfo@kingspan.com

Customer Services:
T. 0345 260 7260
E. customer care@kingspan.com