Kingspan Ferham

Specification sheet Open top cisterns - Rectangular

Features

- Application Storage and supply of cold potable water to an open vented cylinder, or use as expansion tanks in vented heating systems
- Injection-moulded from approved hygenic polypropylene plastic
- Manufactured to BS4213:2004
- KIWA Certificat No. 1602706
- Accessories kit including close fitting lid, backing plate, 60mm insulation jacket and ties available to purchase separately
- 1-Year Guarantee against manufacturing defects





Cap	acity	Height	Width	Depth	Code	Code
	L	(mm)	(mm)	(mm)	CISTERN	KIT
4	18	330	296	442	FC4G	BK4G [†]

Note: As Kingspan maintains a policy of ongoing continuous improvement, these specifications are subject to change without notice. †BK4G does not include Byelaw 30 fittings (lid, insulation jacket & backplate only)

GB Sales Office:

T. 0345 260 0258

E. cylinder.sales@kingspan.com

NI Sales Office:

T: 028 3836 4520

E: cylindersinfo@kingspan.com

Technical Support:

T. 0345 260 0007

E. cylinder.tech-support@kingspan.com

Customer Services:

T. 0345 260 7260

E. customercare@kingspan.com

Wakefield Office:

Kingspan Water & Energy Ltd. Tadman Street, Wakefield, West Yorkshire, WF1 5QU

