
Pre-Slit Weatherproof Insulation



Install +



Our new pre-slit PVC coated insulation provides outstanding protection against freezing, for external boiler condensate pipework. This new design offers a quick and secure 'tape free' installation, with its peel and seal join and its self-adhesive wrap over flap. Fully compliant with the Boiler Installation Standards BS6798:2014, the tough PVC coating is both weatherproof and UV stable.

This insulation is also ideal for use on air source heat pumps or biomass flow and return pipework, to avoid heat loss and meet MIS3005 requirements. To prevent cold bridging use it in conjunction with our Through Wall Sleeve Kit, TW-KIT, to ensure the pipework is fully insulated all the way into the property. Visit our You Tube site for a full installation demonstration: www.youtube.com/user/pumphousepumps

Features

- Avoids heat loss and improves efficiency of the installed air souce heat pump
- 19mm wall insulation with a tough PVC coating
- Suitable for 28mm / 32mm / 22mm pipework

The Package

• 1 x straight 2000mm length of pre-slit 35mm, 28mm or 22mm ID insulation









Part Code	Description
FH-I-1000-35-SLIT	2 metre length of 35mm ID insulation with 19mm wall thickness insulation pre slit seal
FH-I-1000-28-SLIT	2 metre length of 28mm ID insulation with 19mm wall thickness insulation pre slit seal
FH-I-1000-22-SLIT	2 metre length of 22mm ID insulation with 19mm wall thickness insulation pre slit seal

The Pump House sales team are available to answer your questions or queries on this product. Our experts are waiting for your call **+44 (0)115 900 5858** or if you prefer send an email to **sales@pumph.co.uk** or visit **www.pumph.co.uk**

