



Product Fiche

Supplier name	Arada
Product Code	SOL7-S4
Energy Efficiency Class (wood)	A
Direct Heat Output (wood)	7.0 Kw
Indirect Heat Output (wood)	N/A
Energy Efficiency Index (wood)	101.6
The useful energy efficiency at nominal heat output and at minimum load (wood)	77.9 %

Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:

Product should be installed in accordance with local building regulations.
Appliance will become very hot during use.

Dimensions

Width	518.5 mm
Height	551 mm
Depth	387 mm
Flue Diameter	127 mm
Depth from back to centre of top flue	82 mm
Height to centre of rear flue	448 mm
Ideal log length / diameter	330mm / 100mm

Performance – Wood & Solid Fuel

	Wood Fuel	Solid Fuel
Energy Efficiency Class	A	D
Nett Efficiency	77.9 %	81.5 %
Nominal Output	7.0 kW	7.1 kW
Mean Co Emission (@13% O₂)	0.12 %	0.06 %
DIN+ particulate	18 Nmg/m ³	24 Nmg/m ³
Mean NO_x Emission (@13% O₂)	109 Nmg/m ³	120 Nmg/m ³
Mean OGC Emission (@13% O₂)	107 Nmg/m ³	42 Nmg/m ³
Flue Gas Mass Flow	6.2 g/s	4.3 g/s
Flue Gas Temperature	291 °C	326 °C
Typical Fuel load for nominal rated output per hour (kWh/Kg)	1.55(Seasoned hardwood)	1.0 (MSF Maxibrite)

Features

Flexifuel	No
Stove body type	Freestanding
Ecodesign Ready	Yes
Suitable for smoke control areas	Yes
Suitable for direct air connection	No
Suitable for non-combustible 12mm hearth	Yes
Weight gross (packed kg)	TBA Kg
Weight nett (unpacked kg)	TBA Kg

Minimum distance to combustibles

Single Walled Flue, *without* Rear Heat Shield fitted

Rear	650 mm
Side	650 mm
Max hearth temp	53 °C

Single Walled Flue, *with* Rear Heat Shield fitted

Rear	500 mm
Side	900 mm
Max hearth temp	53 °C

Schiedel Twin Walled Flue *with* Rear Heat Shield fitted

Rear	350 mm
Side	650 mm
Max hearth temp	53 °C